



BASIC FEATURES

- Two Stage Cast Iron Pump
- Swedish stainless steel reed valve
- Low oil consumption
- Precise balanced crank shaft and flywheel for low vibration
- Al head with big cooling fin for lower temperature operation
- Belt Driven
- CU Coil Motor
- Grey Tank
- Metal Mesh Guard
- Built-in Schneider Contact and thermal overload relay as mentioned



SPECIFICATIONS:

Model	Phase	Voltage	Tank	HP	Kw	Max. Press. Bar	Bore*Stroke*cyl.	RPM	Displacement L/min	cfm
V0.40/12.5 Two Stage Piston Type	1	220V/60HZ	80 Gal Vertical	5.5	4	12.5	φ90*60*1/φ65*1	1280	488	17.3



autoreach.ph



0962-700-5963



Cavite Light Industrail Park
Brgy. Maguyam Silang Cavite



autoreach.company@yahoo.com



autoreach
company inc.



BASIC FEATURES

- One Stage Cast Iron Pump
- Swedish stainless steel reed valve
- Low oil consumption
- Precise balanced crank shaft and flywheel for low vibration
- AI head with big cooling fin for lower temperature operation
- Belt Driven
- CU Coil Motor
- Grey Tank
- Metal Mesh Guard



SPECIFICATIONS:

Model	Phase	Voltage	Tank	HP	Kw	Max. Press. Bar	Bore*Stroke*cyl.	RPM	Displacement L/min	cfm
V0.25/8 Single Stage Driven Pumps	1	220V/60HZ	40 Gal Horizontal w/ Wheels	3	2.2	10	Ø65*46*2	1235	377	13.3



autoreach.ph



0962-700-5963



Cavite Light Industrail Park
Brgy. Maguyam Silang Cavite



autoreach.company@yahoo.com



autoreach
company inc.